



NOW OFFERING

Screens & Fabricated Metals

A Division of Century Bathworks Inc.



Effortless removal of inserts allows easy cleaning...

Triple Track Combination Storm Window



Designed for home and commercial use:

- Self-Storage of all inserts
- Fingertip action with positive action stops
- Automatic tamper-proof locks
- Top or bottom ventilation
- Multi-positioning of all inserts
- Sturdy reinforced construction
- Fully extruded 6063 heat tempered aluminum
- Concealed metal-to-metal interlocks
- Stainless steel screws and springs
- Adjustable bottom expander
- Wool pile weather stripping
- Fiberglass insect screening 18 x 14 mesh
- Marine glazing
- Individually tested and inspected



Color Options:



White



Black



Bronze



Beige



Green

Visit our website for more information on our products!



The Difference is in the Details



Design incorporates many energy efficient features that ensures top performance!

1. High tempered 6063 T-6 aluminum coupled with chambered frame design - provide unparalleled rigid, ensuring ease of installation and long term durability.
2. Maintenance free baked enamel finish - available in white, beige, bronze, black or green.
3. Double weatherstripped with double finned seals, ensuring a solid barrier against air, water, dust and noise.
4. Integral sash - retaining jambs.
5. Pocketed frame head and sill.
6. Oversized "never-fail" mechanical interlock is double weatherstripped.
7. Marine style sash glazing - cushions glass and ensures weather tightness.
8. Screwed butt corners provides maximum durability.
9. Locking insect screen is available with glare-free fiberglass or charcoal anodized aluminum mesh.
10. Ease of operation - thoughtful design allows for simple raising, lowering, and removal of sash and screen. Sure grip slide bolts lock securely into the closed, open or intermediate positions.

Peak Performance

Available Styles:

- Double Hung
- Slider (2-Panel + 3-Panel)
- Picture Window

Glazing:

- Clear annealed glass (standard)
- Hard Coat Low E Glass
- Tempered Glass
- Lexan (polycarbonate)


Tests prove storm windows offer Unprecedented energy efficiency and durability.

- Air infiltration rate* - 0.07 cfm/ft**
- Structural loading - 134 mph.
- Testing done by independent testing laboratory in accordance with ANSI/AAMA 1002.10 "Voluntary Specifications for Aluminum Windows"

* Air infiltration at 1.56 psf or 25 mph wind.

** cfm/ft: cubic feet of air per minute, per foot of window crack perimeter

Standard Maintenance Free Finishes



Custom Maintenance Free Finishes

Note: Actual colors may vary slightly from brochure due to printing